MOTORS FOR SCREWDRIVING APPLICATIONS WITH SLIP-TRK CLUTCH

Data sheet
ALFB2R FR

ALFB FR SERIES - Reversible

WATT: 160 / CONSUMPTION: 400 Nl/1'

Data measured at pressure of 6 bar - Minimum supply hose diameter: 6 mm



1. 1/4" hexagonal bit holder connection
2. Grip zone
3. Air inlets
4. Air exhaust

Technical specification

Right rotation - Model	ALFB2R FR
Right rotation - Code	8604212
No-load speed - rpm/min	900
Torque Nm - Nm	3,6
Screws tightening	M3-M4
Clutch spring	White
Clutch unit	7311141

Form features

Allow the tightening torque to be adjusted through a friction clutch.
Output shaft with axial sliding (3 mm), on request without scrolling.
Standard bit holder coupling 1⁄4" (6.35 mm).

MOTORS FOR SCREWDRIVING APPLICATIONS WITH SLIP-TRK CLUTCH

Data sheet
ALFB2R FR

ALFB FR SERIES - Reversible

WATT: 160 / CONSUMPTION: 400 Nl/1'

Data measured at pressure of 6 bar - Minimum supply hose diameter: 6 mm

Overall dimensions



Model	Code	A	B	C	D	E	F	U	V	Y	Z
ALFB2R FR	8604212	129,7	46,7	34	38	47	58	9,5	11	1/4"	3/8"