Screwdrivers with torque control - Clutch type: ACCU-TRK

Data sheet
AN15/600

ANGLE SCREWDRIVERS - Lever start - AN series
WATT: 220
Square coupling: 1/2”



Description

This clutch type stops the power supply to the motor and stops tool rotation when a preset torque is reached. The clutch enables high- precision tightening torques (+/- 15% in flexible fastenings and +/- 10% in rigid fastenings), increases productivity and eliminates waiting times. The system prevents vibration of the operator’s hand. The clutch range is adjusted using one of the variety of springs available. Screwdrivers of the ACCU-TRK® family are supplied with a clutch spring enabling use of the maximum torque. If you require a lower adjustment range, request a spring with a lower rating.

Technical specification

Model	AN15/600
Code	8304021
No-load speed - tours/min	595
Screw tightening - Metal	M5 - M6
Torque - Nm	3,5-12
Spring colour	Silver
Length - mm	360
Body - ø mm	44
Air connection	1/4”GAS
Weight - Kg	1,7
Hose - ø min mm	8
Air consumption - Nl/min	430

Screwdrivers with torque control - Clutch type: ACCU-TRK

Data sheet
AN15/600

ANGLE SCREWDRIVERS - Lever start - AN series

WATT: 220

Square coupling: 1/2”

Overall dimensions

