

Screwdrivers with torque control - Clutch type: ACCU-TRK

STRAIGHT SCREWDRIVERS - Push start - AMI Series

WATT: 70

Hexagonal coupling: 1/4"

Data sheet
AMI22AT



Description

This clutch type stops the power supply to the motor and stops tool rotation when a preset torque is reached. The clutch enables high-precision tightening torques (+/- 15% in flexible fastenings and +/- 10% in rigid fastenings), increases productivity and eliminates waiting times. The system prevents vibration of the operator's hand. The clutch range is adjusted using one of the variety of springs available. Screwdrivers of the ACCU-TRK® family are supplied with a clutch spring enabling use of the maximum torque. If you require a lower adjustment range, request a spring with a lower rating.

Technical specification

Model	AMI22AT
Code	8301052
No-load speed - rpm/min	1200
Screw tightening - Metal	M3 - M4
Torque - Nm	0,4-1,8
Spring colour	Blue
Length - mm	215
Body - ø mm	33
Air connection	1/8" GAS
Weight - Kg	0,5
Hose - ø min mm	6
Air consumption - NI/min	300

Screwdrivers with torque control - Clutch type:
ACCU-TRK

STRAIGHT SCREWDRIVERS - Push start - AMI Series

WATT: 70

Hexagonal coupling: 1/4"

Data sheet
AMI22AT

Overall dimensions

