MOTORS WITH POWER UP TO 850 W

T SERIES - Reversible

WATT: 740 / CONSUMPTION: 1100 Nl/1'

Data measured at pressure of 6 bar - Minimum supply hose diameter: 12 mm

Data sheet

THR



1. Cylindrical keyed shaft
2. Grip zone
3. Air inlets
4. Air exhaust


Technical specification


- Model	THR
- Code	8731201
Speed rpm - No-load	13000
Speed rpm - at Max Power	6700
Torque Nm - at Max Power	1
Torque Nm - Stall Torque	1,6

Form features

The normal delivery condition:
cylindrical shaft and body as shown in the photo.
Optional:
Shaft
- threaded - indication /AF (left rotation excluded - subject to checks for reversible)
- conical - indication /AC
- with collets - indication / AP

Characteristic curves





MOTORS WITH POWER UP TO 850 W

T SERIES - Reversible

WATT: 740 / CONSUMPTION: 1100 Nl/1'


Data measured at pressure of 6 bar - Minimum supply hose diameter: 12 mm

Data sheet
THR

Permissible radial and axial loads

Model	Code	Fr (N)	Fa (N)	Co (N)
THR	8731201	1300	2350	4750

Overall dimensions



Model	Code	A	B	C	D	F	G	H	I	L	M	N	O	P	Q
THR	8731201	199,5	31,5	48	54	31,5	14	/	/	M6	1/2"x20UNF	15,5	21	B12	26,5