

## ELECTRONIC SCREWDRIVERS

With transducer- Twin control of feed torque and detected

Data sheet  
**ACE-400-150 SCC**



1. Engine
2. Transducer
3. Flange
4. Shaft with compensator
5. Main power switch
6. Touchscreen Control Panel
7. Control lights

### Description

Screwdrivers with a built-in transducer have a screw driving torque precision of +/- 1% of the scale range (e.g. a 80 Nm screwdriver has a precision of +/- 0.8 Nm); torque precision is independent of the maximum torque requested.

The repeatability precision when screw driving rigid fastenings is 1% for the transducer version and 3% for the versions without transducer. To obtain the best results the screw driving units should be secured using suitable clamping systems.

The ACE screw driving units have a single screw driving spindle and a controller unit for each spindle.

- Semi-graphics LCD display with 4 lines of 20 characters each line. Built-in membrane keyboard. Up to 5 screw driving programs of 5 steps each can be set, stored and called up from the keyboard.

Each program step can be programmed by the user as required with the following values:

- i. Speed / Direction of rotation
- ii. Torque or Angle to be reached
- iii. Time limit or degree limit range within which the set torque/angle must be reached.

- Up to 1024 screw driving operations can be stored to memory.

- Torque curve of the last screw driving (resolution 0.01 seconds) can be stored to memory.

- RS-232 C connection to PC for reading screw driving data on-line - RS-232 C connection to PC for transferring memory data.

### Technical specification

Model	ACE-400-150 SCC
Code	8306806
No-load speed - rpm	150
Torque - Nm	18 - 150
- dB(A)	62
Weight - Kg	5,8
Length - mm	588,5
Stroke - mm	50