

Screwdrivers - Clutch type: SLIP-TRK

GUN SCREWDRIVERS - ERVIT series

WATT: 130

Hexagonal coupling: 1/4"

Data sheet

ERVIT33



Description

Slip clutch. In this case the clutch is adjusted using the Allen keys provided. This solution is ideal for those situations where a simple system for adjusting the tightening torque is required. Various adjustment ranges can be obtained by simply changing the springs. Models for use in wider than standard ranges are supplied with an extra spring. In those cases where frequent changes to tightening torques are required, we recommend that you use a tool equipped with a series of clutch units each set to a particular torque; when you need to change torque setting, just change the clutch unit. When ordering, use the codes indicated in the table.

Technical specification

Screwdrivers - Clutch type: SLIP-TRK

GUN SCREWDRIVERS - ERVIT series

WATT: 130

Hexagonal coupling: 1/4"

Model	ERVIT33
Code	8302063
No-load speed - rpm/min	450
Screw tightening - Metal	6
Screw tightening - Wood	4x40
Torque - Nm	6,5
Spring colour - *	Yellow
Length - mm	180
Body - ø mm	38
Air connection	1/4"GAS
Weight - Kg	1,05
Hose - ø min mm	6
Air consumption - NI/min	420

Data sheet
ERVIT33

Overall dimensions

Screwdrivers - Clutch type: SLIP-TRK

GUN SCREWDRIVERS - ERVIT series

WATT: 130

Hexagonal coupling: 1/4"

Data sheet

ERVIT33

