

Screwdrivers with torque control - Clutch type:

ACCU-TRK

GUN SCREWDRIVERS - Button /push start - ERGOVIT series

WATT: 220

Hexagonal coupling: 1/4"

Data sheet
ERGOVIT70AT



Description

This clutch type stops the power supply to the motor and stops tool rotation when a preset torque is reached. The clutch enables high-precision tightening torques (+/- 15% in flexible fastenings and +/- 10% in rigid fastenings), increases productivity and eliminates waiting times. The system prevents vibration of the operator's hand. The clutch range is adjusted using one of the variety of springs available. Screwdrivers of the ACCU-TRK® family are supplied with a clutch spring enabling use of the maximum torque. If you require a lower adjustment range, request a spring with a lower rating.

Technical specification

Model	ERGOVIT70AT
Code	8302314
No-load speed - rpm/min	280
Screw tightening - Metal	M6 - M8
Torque - Nm	4,8-14,6
Spring colour	Gold
Length - mm	237
Body - ø mm	41
Air connection	1/4" GAS
Weight - Kg	1
Hose - ø min mm	8
Air consumption - NI/min	420

Screwdrivers with torque control - Clutch type:
ACCU-TRK

GUN SCREWDRIVERS - Button /push start - ERGOVIT series

WATT: 220

Hexagonal coupling: 1/4"

Data sheet
ERGOVIT70AT

Overall dimensions

